

■Please fill out the format with requests and send to: sales@fujicon.com

Date		Target date	
------	--	-------------	--

Contact person		Section	
Company name		Fax number	
Telephone number		E-mail	

Item	Example	Requirements
Set	PC, TV, Power Supply, Audio, Toy, etc	
Application	Smoothing, Filtering, By-pass, Coupling, etc	
Production	Quantity, Prototype plan, Production plan	
Environment friendly	RoHS, Halogen-free, etc	
Target price	Prototype price, Production price	
Type	Chip type aluminum electrolytic capacitors Radial lead type aluminum electrolytic capacitors Snap-in type aluminum electrolytic capacitors	
Rated voltage	6.3 ~ 450 WV (V.D.C.)	
Rated capacitance	0.1 ~ 68000 μ F	
Capacitance tolerance	\pm 20%(M), \pm 10%(K)	
Dimension	Lead pitch \varnothing D(Diameter) x L(Length)	
Temperature range	-25 $^{\circ}$ C~85 $^{\circ}$ C, -40 $^{\circ}$ C~85 $^{\circ}$ C -25 $^{\circ}$ C~105 $^{\circ}$ C, -40 $^{\circ}$ C~105 $^{\circ}$ C	
Ripple current	Current, Frequency	
Operation condition	Operating time per day, Temperatures	
Life time	Guaranteed life, Expected life	
Life time	Dip, Flow, Reflow Soldering temperature, Seaking time, Times Peak temperature conditions, Preheating	
Other quality conditions	Impedance, Leakage current	
Packaging style	Bulk (for radial lead type) Lead cutting & Forming (for radial lead type) Taping (for radial lead type)	
Other conditions	Other specific requirements	