

LK Series

LOW LEAKAGE CURRENT, WIDE TEMPERATURE RANGE


低漏電流寬溫品

- Wide operating temperature range of -40~+105°C
適用於 -40~+105°C 的寬溫範圍

- Low leakage current series
低漏電流系列

- For Hi-Fi sound audio systems
適用於高保真音響設備



- Comply with the RoHS & REACH
符合 RoHS 與 REACH



□ SPECIFICATIONS 特性表

Items 項目	Characteristics 主要特性																
Operation Temperature Range 使用溫度範圍	-40 ~ +105°C																
Voltage Range 額定工作電壓範圍	10 ~ 50V																
Capacitance Range 靜電容量範圍	0.1 ~ 330μF																
Capacitance Tolerance 靜電容量允許偏差	±20% at 120Hz, 20°C																
Leakage Current 漏電流	Leakage current ≤ 0.002CV or 0.4μA, whichever is greater (after 2 minutes application of rated voltage at 20°C) 漏電流 ≤ 0.002CV 或 0.4μA, 取較大值 (在 20°C 環境中施加額定工作電壓 2 分鐘後) C: Nominal capacitance (μF) 標稱靜電容量, V: Rated voltage (V) 額定電壓																
Dissipation Factor (tan δ) 損耗角正切	When nominal capacitance is over 1000μF, tan δ shall be added 0.02 to the listed value with increase of every 1000μF. 當標稱靜電容量大於 1000μF, 其標稱靜電容量每增加 1000μF, 損耗角正切增加 0.02. Measurement frequency 測試頻率: 120Hz, Temperature 測試溫度: 20°C <table border="1"><tr><td>Rated Voltage (V) 額定工作電壓</td><td>10</td><td>16</td><td>25</td><td>35</td><td>50</td></tr><tr><td>tan δ (max.) 最大損耗角正切</td><td>0.20</td><td>0.16</td><td>0.14</td><td>0.12</td><td>0.10</td></tr></table>					Rated Voltage (V) 額定工作電壓	10	16	25	35	50	tan δ (max.) 最大損耗角正切	0.20	0.16	0.14	0.12	0.10
Rated Voltage (V) 額定工作電壓	10	16	25	35	50												
tan δ (max.) 最大損耗角正切	0.20	0.16	0.14	0.12	0.10												
Stability at Low Temperature 低溫特性	Measurement frequency 測試頻率: 120Hz <table border="1"><tr><td>Rated Voltage (V) 額定工作電壓</td><td>10</td><td>16</td><td>25 ~ 50</td></tr><tr><td>Impedance Ratio Z(-25°C) / Z(20°C)</td><td>3</td><td>2</td><td>2</td></tr><tr><td>阻抗比 Z(-40°C) / Z(20°C)</td><td>6</td><td>6</td><td>4</td></tr></table>					Rated Voltage (V) 額定工作電壓	10	16	25 ~ 50	Impedance Ratio Z(-25°C) / Z(20°C)	3	2	2	阻抗比 Z(-40°C) / Z(20°C)	6	6	4
Rated Voltage (V) 額定工作電壓	10	16	25 ~ 50														
Impedance Ratio Z(-25°C) / Z(20°C)	3	2	2														
阻抗比 Z(-40°C) / Z(20°C)	6	6	4														
Load Life 高溫負荷特性	After 1000 hours application of the rated voltage at 105°C, they meet the characteristics listed below. 在 105°C 環境中施加額定工作電壓 1000 小時後, 電容器的特性符合下表的要求。 <table border="1"><tr><td>Capacitance Change 靜電容量變化率</td><td>Within ±20% of initial measured value 初始值的±20% 以內</td></tr><tr><td>Dissipation Factor 損耗角正切</td><td>≤200% of initial specified value 不大於規範值的 200%</td></tr><tr><td>Leakage Current 漏電流</td><td>≤initial specified value 不大於規範值</td></tr></table>					Capacitance Change 靜電容量變化率	Within ±20% of initial measured value 初始值的±20% 以內	Dissipation Factor 損耗角正切	≤200% of initial specified value 不大於規範值的 200%	Leakage Current 漏電流	≤initial specified value 不大於規範值						
Capacitance Change 靜電容量變化率	Within ±20% of initial measured value 初始值的±20% 以內																
Dissipation Factor 損耗角正切	≤200% of initial specified value 不大於規範值的 200%																
Leakage Current 漏電流	≤initial specified value 不大於規範值																
Shelf Life 高溫貯存特性	After leaving capacitors under no load at 105°C for 1000 hours, they meet the specified value for load life characteristics listed above. 在 105°C 環境中無負荷放置 1000 小時後, 電容器的特性符合高溫負荷特性中所列的規定值。																
Marking 標識	Printed with black colour on orange sleeve (PVC) or printed with white colour on green sleeve (PET). 桔紅色膠管黑字印刷 (PVC) 或綠色膠管白字印刷 (PET)。																

□ DRAWING 外形圖 (Unit: mm)



ØD	5	6.3	8 (L≤11.5)	8 (L≥16)	10
P	2.0	2.5	3.5		5.0
Ød		0.5		0.6	
β			1.5		

Note: All design and specifications are for reference only and is subject to change without prior notice. If any doubt about safety for your application, please contact us immediately for technical assistance before purchase.

注：以上所提供的設計及特性參數僅供參考，任何修改不作預先通知。如果在使用上有疑問，請在採購前與我們聯繫，以便提供技術上的協助。

CAT.2019/V4

LK Series

□ DIMENSIONS & MAXIMUM PERMISSIBLE RIPPLE CURRENT 規格尺寸及最大允許紋波電流

μF	WV Code 代碼	10		16		25		35		50	
		1A		1C		1E		1V		1H	
0.47	R47									5 x 11	9.6
0.68	R68									5 x 11	11
1	010									5 x 11	14
1.5	1R5									5 x 11	17
2.2	2R2									5 x 11	21
3.3	3R3									5 x 11	25
4.7	4R7									5 x 11	30
6.8	6R8									5 x 11	36
10	100									5 x 11	44
15	150							5 x 11	54	5 x 11	62
22	220			5 x 11	54	5 x 11	57	5 x 11	61	5 x 11	68
33	330			5 x 11	64	5 x 11	69	5 x 11	75	6.3 x 11.5	90
47	470	5 x 11	70	5 x 11	79	5 x 11	82	6.3 x 11.5	100	6.3 x 11.5	110
68	680	5 x 11	96	5 x 11	108	5 x 11	115	6.3 x 11.5	156	8 x 11.5	150
100	101	5 x 11	105	5 x 11 (6.3 x 11.5)	115 (125)	6.3 x 11.5	135	8 x 11.5	170	8 x 11.5	180
150	151	5 x 11	150	6.3 x 11.5	175	8 x 11.5	190	10 x 12	245	10 x 12	285
220	221	6.3 x 11.5	175	6.3 x 11.5	205	8 x 11.5	230	10 x 12	300	10 x 16	390
330	331	6.3 x 11.5	245	8 x 11.5	285	8 x 11.5	345	10 x 16	400		
470	471	8 x 11.5	355	8 x 11.5	365	10 x 12	470	10 x 20	565	Case size 尺寸	Ripple current 紋波電流
1000	102	10 x 12	600	10 x 16	745	10 x 20	850				

• Case size $\varnothing D \times L$ (mm), ripple current (mA rms) at 105°C, 120Hz • 尺寸 $\varnothing D \times L$ (mm), 紋波電流(mA rms)於 105°C, 120Hz

- Please refer to page 19 "Taping Specifications" & page 21 "Lead Forming & Cutting" about the taped or formed product spec. 編帶與引線成型標準請查閱第 19 頁 “編帶標準” 及第 21 頁 “引線成型與剪腳”。
- Please refer to page 20 "Packaging Specifications" for the minimum package quantity. 最小包裝數量請查閱第 20 頁 “包裝標準”。
- Please refer to page 16 for the Part Number System. 產品編碼規則請查閱第 16 頁。

Note: All design and specifications are for reference only and is subject to change without prior notice. If any doubt about safety for your application, please contact us immediately for technical assistance before purchase.

注：以上所提供的設計及特性參數僅供參考，任何修改不作預先通知。如果在使用上有疑問，請在採購前與我們聯繫，以便提供技術上的協助。

CAT.2019/V4